

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 February 2005 (10.02.2005)

PCT

(10) International Publication Number
WO 2005/012674 A1

(51) International Patent Classification⁷: **E05B 47/00,**
63/08

Domenlco [IT/IT]; c/o Serrature Meroni S.p.A., Via
Sabotino, 14/C, I-04011 Aprilia (IT).

(21) International Application Number:
PCT/EP2004/051464

(74) Agents: **LONG, Giorgio et al.; JACOBACCI & PART-**
NERS S.p.A., Via Senato, 8, I-20121 MILANO (IT).

(22) International Filing Date: 12 July 2004 (12.07.2004)

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
TO2003A000546 15 July 2003 (15.07.2003) IT

(71) Applicant (*for all designated States except US*): **SERRA-**
TURE MERONI S.p.A. [IT/IT]; Via Diaz, 21, I-20054
Nova Milanese (MILANO) (IT).


(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **SEMENTILLI,**

[Continued on next page]

(54) Title: **ELECTRIC MORTISE LOCK**



(57) Abstract: A body (14) of the electric lock, embedded in a jamb of a fixed frame, contains an electromechanical release device comprising a loading bolt (28) suitable to be retracted in the body (14). A pusher (34) is movable between a retracted position in the body (14) and a forward position in a selvage (26) to expel from the selvage (26) the nose (20) of the lock and release the latter. There are provided elastic means (52) for the pusher (34) to be returned to the forward position. An escapement system (44) is suitable to hold the pusher (34) at the retracted position. A kinematic mechanism (46) interlocks the loading bolt (28) and the escapement system (44) such that, when the loading bolt (28) is caused to retract, the pusher (34) is held at the retracted position by the escapement system (44); when an electromagnet (42) is excited, the escapement system (44) releases the pusher (34), which is snapped to the forward position to expel the nose (20).

European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*